

DS35HG DOUBLE SCISSOR LIFT

Standard hot-dip galvanizing with additional powder

3.5 ELECTRO-HYDRAULIC

The low-profile double scissor lift DS35HG has been specially designed for the service and repair sector. The newly designed flexible mounting platforms allow for a broad mounting range.



HIGHLIGHTS IN DETAIL







or



Rolling Ramp Mounting Frame

Cleanly arranged and robust push safe operation of the lifting platform.

It may be places left or right Tube length between



stored on the integrated tray

Pre assembled control panel has a quiet running hydraulic thus contributes significantly to

Maintenance friendliness comes first: the side panels can be removed on all 4 sides, the electrical components are located underneath the hinged operating and writing console.

Model	DS35HG
Rated Load Capacity	3500kg
Stroke	1945mm
Platform Length	1500mm - 2160mm
Total Length	2160mm
Overall Width	2060mm - 2160mm
Lifting Time Loaded	40 sec
Lowering Time Loaded	40 sec
Ascending Height / Rest Height	105mm
Engine Power	3kW
Power Supply Voltage	400 V, 50Hz
Weight	885kg

ACCESSORIES











- Installation kit for underfloor installation without 1 angle iron frame.
- Installation kit for underfloor installation, hot-dip galvanized with angled iron frame.
- Additional ramps for sports cars, hot galvanised and 3 powdercoated, length 860 mm (1 set / 4 pieces.)
- Crossbar for supporting vehicles whose mounting 4 points are located in the intermediate area of the platforms.
- Rotary Rubber Block, pyramidal truncated with grip 5 pads, height 30 mm (1 set / 4 pieces.)
- Rotary Rubber Block pyramidal truncated with grip 6 pads, height 70 mm (1 set / 4 pieces.)
- 7 Power Kit (230 V socket outlet.)



MAIN OFFICE: UNIT 7, MANOR BUSINESS PARK, WOODFORD HALSE, NORTHAMPTONSHIRE, NN11 3UB.

(01295) 768373 (@) enquiries@bullworthy.co.uk 🔇 www.bullworthy.co.uk