## **TECHNIQUE T2210-PRO Tyre Changer**

The Technique T2210-PRO Fully automatic 24" tyre changer will meet the highest of demands from any operator.

The side assist arm is supplied with two adaptor arms with an option of an extra roller for lifting the bottom bead.

- Side bead breaker with adjustment for wider wheels. .
- High turret for up to 15" wide wheels. .
- 10"-24" turntable clamping. •
- Plastic inserts for rim protection, plastic jaws and . bead breaker cover.
- Single phase motor 3 pin plug. •
- Air supply 8-10 bar 115-145 psi. .



**Optional quick** release kit.

**Optional plastic** head.

**Optional bead** 

roller.



**Optional raised** spoke head.


Motor	0,75 Kw - 230/400V (50-60Hz) - 3ph
Chuck rotation speed (rev/min)	7,3 rpm / 6,5/13 rpm
Max torque to chuck	1200 Nm (885 FtLbs)
External clamping	11"-22"
Internal clamping	13"-24.5"
Tool working span	8"-32"
Max tyre diameter	1050 mm (41")
Max rim width	318 mm (15")
Bead breaker cylinder power @ 12 bar	3600 kg (8000 lbs)





1050mm

(41")





381mm (15")

**Protection covers** for bead breaker & jaws included.



Pneumatic side assist arm.



Two position fast bead breaker.



Easy removable pedal box.



## WANT TO FIND OUT MORE? GET IN TOUCH WITH US TODAY!



(01295) 768373 ወ enquiries@bullworthy.co.uk ወ www.bullworthy.co.uk



