


TTECHNIQUE T2225-M2 Tyre Changer


The Technique T2225-M2 tyre changer is equipped with an innovative leverless tool (patented) that allows to work quickly and effortlessly even on new-concept and ultra-low profile tires, RUN-FLAT.

Complete with a double roller bead breaker pushing system, the tyre bead is broken quickly and safely by two opposed and synchronised disks. The center post locking with floating plate (patented), suitable also for reverse rims, offers a self-locking mechanism that reduces the effort of the operator.

The wheel rotation can be controlled as desired by the operator through the inverter motor with speed limiter to protect the tyre from excessive forces (0 - 15 rpm).



Double roller bead breakers.



Cable free design.



Assisted synchronised arms.





Upper mounting head.



User friendly console.



Optional wheel lift.



Bead Break Force	12 kN
Rotation Speed	0 / 15 rpm
Power Inverter Motor	1.5 kW
Chuck Motor Rating	0.75 kW
Power Supply	777-230 V 50 - 60 Hz
Phases	1
Fuse Protection	16
Air Supply	8 bar
Air Supply Max	10 bar



WANT TO FIND OUT MORE? GET IN TOUCH WITH US TODAY!



(01295) 768373



enquiries@bullworthy.co.uk



www.bullworthy.co.uk