

**Rotary**  
®

# SGL35

## TWO POST LIFT



**BULLWORTHY**  
THE GARAGE EQUIPMENT SPECIALISTS

# SGL35 FEATURES AT A GLANCE

- 1 3164mm minimum ceiling height.
- 2 Quick-fit telescopic pads provide a high level of height adjustment.
- 3 The single electro-hydraulic power unit delivers energy-efficient, quiet, and reliable operation.
- 4 Arms auto-lock during lifting and unlock when lowered, with manual release for easy operation.
- 5 The free overhead design makes the lift ideal for low-ceiling workshops.



## OPTIONAL ACCESSORIES



- 1 Support Kit for delivery trucks/vans, 4 x U-support.
- 2 Rotary Adaptor Extension Kit , 4 x 89mm, 4 x 127mm, with 2 organizer racks.
- 3 4 x 200mm, with 2 organiser racks.
- 4 4 x U-support for delivery trucks/vans.
- 5 Pick-up adapter Tesla.

Number Of Columns	2
Drive Mode	Electro Hydraulic
Control	Manual
Installation Type	Surface Mounted
Rated Load Capacity	3500kg
Maximum Lifting Height (With AK Kit)	1828mm
Lifting Time	40 Seconds
Rotary Plate Height Minimum	114mm
Rotary Plate Height Maximum	170mm
Column Height	2926mm
Drive Through Width	2388mm
Minimum Ceiling Height	3164mm
Recommended Ceiling Height	3260mm
Support Arm Design	Symmetrical
Motor Power	1 x 2.2kW
Power Supply	400V   50-60Hz
Width	3320mm
Height	3164mm

